


PAC系列空气过滤组合(二联件)



符号




订购码

PAC	2010	-	02	D
系列代号	壳体代号		螺纹代号	排水方式
	1010 2010 3010 4010 5010		M5:M5 02:1/4" 03:3/8" 04:1/2" 06:3/4" 10:1"	空白:手动排水 A:差压排水 D:自动排水

技术参数

手动排水型	PAC1010-M5	PAC2010-02	PAC3010-02	PAC3010-03	PAC4010-04	PAC4010-06	PAC5010-06	PAC5010-10
自动排水型	PAC1010-M5D	PAC2010-02D	PAC3010-02D	PAC3010-03D	PAC4010-04D	PAC4010-06D	PAC5010-06D	PAC5010-10D
接管口径	M5×0.8	1/4	1/4	3/8	1/2	3/4	3/4	1
压力表口径	1/16	1/8	1/8	1/8	1/4	1/4	1/4	1/4
额定流量	90	500	2000	2000	4000	4500	5000	5000
环境及流体温度	5-60℃							
保证耐压力	1.5Mpa (15.3kgf/cm ²)							
最高使用压力	1.0Mpa (10.2kgf/cm ²)							
过滤孔径	5 μm							
建议用油	透平1号油							
杯材料	聚碳酸酯							
杯防护罩	PAC1000~2000(无) PAC3000~5000(有)							
调压范围	PAC1000:0.05~0.7Mpa (0.51~7.1kgf/cm ²)				PAC2000~5000:0.05~0.85Mpa (0.51~8.7kgf/cm ²)			
阀型	带溢流型							
组件 过滤减压阀	PAW1000	PAW2000	PAW3000	PAW3000	PAW4000	PAW4000	PAW5000	PAW5000
组件 油雾器	PAL1000	PAL2000	PAL3000	PAL3000	PAL4000	PAL4000	PAL5000	PAL5000
重量	0.22	0.66	0.98	0.98	1.93	1.99	3.2	3.2

外形尺寸



型号	口径	A	B	C	D	E	F	G	H	J	K	L	M	N	P	B
PAC1010	M5×0.8	58	109.5	50.5	25	26	25	29	20	4.5	7.5	5	18	16	38.5	130
PAC2010	1/4"	90	164.5	78	40	56.8	30	45	24	5.5	8.5	5	22	23	50	187.5
PAC3010	1/4", 3/8"	117	211	92.5	53	60.8	41	58.5	85	7	11	7	34	26	70.5	248.5
PAC4010	3/8", 1/2"	154	262.5	112	70	70.5	50	77	40	9	13	7	42	33	88	300
PAC4010-06	3/4"	164	267	114	70	70.5	50	82	40	9	13	7	46	36	88	304
PAC5010	3/4", 1	195	338	116	90	75.5	69.8	97.5	50	12	16	11	55	40	115	—