


SRLF系列双筒回油管过滤器

符号





订购码

SRLF	BH	60	1	P
系列名称	介质	公称流量	过滤精度	发讯器
双筒回油管路过滤器	BH:水-乙二醇 空白:一般液压油	见下表	见下表	P:带CMS型发讯器 空白:不带发讯器



技术参数

型号	公称流量 (L/min)	过滤精度 (μm)	通径 (mm)	公称压力 (MPa)	压力损失 (Mpa)		发讯装置功率	重量 (kg)	滤芯型号
					Initial	Max.			
SRLF-60×*P	60	1	25	1.6	≤0.08	0.35	24V/48W	13.2	SFX-60×*
SRLF-110×*P	110		25						SFX-110×*
SRLF-160×*P	160	3	40						SFX-160×*
SRLF-240×*P	240	40	SFX-240×*						
SRLF-330×*P	330	5	50						SFX-330×*
SRLF-500×*P	500	10	50						SFX-500×*
SRLF-660×*P	660	20	80						SFX-660×*
SRLF-850×*P	850	80	80						SFX-850×*
SRLF-950×*P	950	30	100						SFX-950×*
SRLF-1300×*P	1300	100	100						SFX-1300×*

外形尺寸



型号	尺寸 (mm)																								
	DN	D	D1	d	d0	f	b1	A2	h1	B1	B	L1	L2	L3	b2	h2	h3	h4	A3	b3	L	A1	H*	H1	
SRLF-60×*P	25	92	68	50	11			98	60	100	168	232	204	160	4	65	16	20	90	11	316	200	258	222	
SRLF-110×*P																								289	
SRLF-160×*P	40	120	92	72	13.5	2	14	125	76	120	230	350	310	250	6	75	20	30	120	14	405	270	361	293	
SRLF-240×*P																								352	
SRLF-330×*P	50	140	110	90				145	90	130	254	380	340	280	90							486	310	395	368
SRLF-500×*P																									449



型号	尺寸 (mm)																							
	DN	D	D1	d	d0	f	b1	A2	h1	B1	B	L1	L2	L3	b2	h2	h3	h4	A3	b3	L	A1	H	H1
SRLF-660×*P	80	200	160	133	17.5	3	20	205	115	170	325	520	480	410	6	150	25	30	160	18	654	440	790	548
SRLF-850×*P																								630
SRLF-950×*P	100	220	180	158				225	132	190	360	630	560	470	6	130	30	40	300	22	774	520	840	609
SRLF-1300×*P																								728